



# bibliotheca RFID tag™ square

ISO 15 693, ISO 18 000-3 Mode 1, NXP ICode SLIX2  
Item Code: TAG000010

## mechanical dimensions

<b>A1 x A2</b>	<b>Antenna size</b>	47 x 47 mm	± 0,5 mm	1,850 x 1,850 in
<b>B1 x B2</b>	<b>Die-cut size</b>	50 x50 mm	± 0,2 mm	1,969 x 1,969 in
<b>C</b>	<b>Web width</b>	54 mm	± 0,5 mm	2,126 in
<b>D</b>	<b>Pitch, length per piece MD</b>	56 mm	± 1,5 mm	2,205 in
<b>E</b>	<b>Die-cut to web edge</b>	2 mm	± 1,5 mm	0,079 in
<b>G</b>	<b>Antenna to die-cut (MD)</b>	1,5 mm	± 1,5 mm	0,059 in
<b>H</b>	<b>Antenna to die-cut (CD)</b>	1,5 mm	± 1,5 mm	0,059 in
<b>U</b>	<b>Die-cut corner radius</b>	3 mm		0,118 in
	<b>Thickness of the IC</b>	127 µm	± 15 %	
	<b>Overall thickness of transponder package (excluding IC and siliconized paper)</b>	195 µm	± 10 %	
	<b>Thickness of the siliconized paper</b>	56 µm	± 5 %	

## electrical characteristics

<b>Integrated Circuit (IC)</b>	NXP ICode SLIX2
<b>Air interface protocol</b>	ISO 15 693, ISO 18 000-3 Mode 1
<b>Operating frequency</b>	13,56 MHz
<b>Unloaded resonance frequency</b>	14,10 MHz ± 0,35 MHz
<b>Memory</b>	2.5k bits user memory

## general characteristics of transponder

<b>Operating temperature (electronics parts)</b>	-40 °C / +85 °C	-40 °F / 185 °F
<b>ESD voltage immunity</b>	± 2 kV peak HBM	
<b>Shelf life: From the date of manufacture 2 years in</b>	15 °C / 25 °C, 50 % RH	59 °F / 77 °F, 50 % RH
<b>Bending diameter (D)</b>	> 50 mm, tension less than 10 N	

## delivery form

<b>Transponder format</b>	Die-cut
<b>Transponder face material</b>	Mid-gloss paper 70 (ISO 9706 compliant)
<b>Transponder backing material</b>	Siliconized Paper 56
<b>Transponder antenna material</b>	Aluminum, crimped coil
<b>Transponder adhesive</b>	Neutral pH Radiation Cured UV Acrylic
<b>labelling temperature</b>	min. +0 °C, min. 32 °F
<b>usage temperature</b>	-20 °C - 80 °C, -4 °F - 176 °F
<b>peel</b>	min. 10 N / 25 mm (FTM 1)
<b>Final inspection</b>	100 %, known faulty ones marked
<b>Minimum delivery yield</b>	97 %
<b>Printability</b>	Flexography and TTR with selected ribbons. Do not print over IC area

## delivery details

<b>Appearance</b>	Single row reel form
<b>Reel core</b>	Paper core inner diameter 76 mm (3 in)
<b>Transponder alignment</b>	Chip at rear of transponder
<b>Winding of the reel</b>	Face out
<b>Standard reel size</b>	2000 pcs/reel, Diameter:< 205 mm
<b>Package size</b>	6000 pcs/box, Deliveries only in full packages, 3 rolls per box

## bibliotheca label performance guarantee

All bibliotheca RFID tag™ products must pass accelerated aging testing at 85°C and at 85% humidity for 15 weeks which included performance testing. Our entire range of RFID tag™ products, when handled according to our recommended practices, are guaranteed for the lifetime of the item to which they are affixed. Data Retention guaranteed for 50 years with a minimum of 100,000 read/write cycles.

Although we make every effort to ensure information is correct at the time of release, it is possible that specifications and features may vary or change over time. bibliotheca therefore makes no representations or warranties as to the completeness or accuracy of the information contained within this document.

 **bibliotheca**<sup>®</sup>  
transforming libraries