



# bibliotheca RFID tag™ rectangleClear

ISO 15 693, ISO 18 000-3 Mode 1, NXP ICode SLIX2

Item Code: TAG000009

## mechanical dimensions

<b>A1 x A2</b>	<b>Antenna size</b>	45 x 76 mm	± 0,5 mm	1,772 x 2,992 in
<b>B1 x B2</b>	<b>Die-cut size</b>	49 x 81 mm	± 0,2 mm	1,929 x 3,189 in
<b>C</b>	<b>Web width</b>	53 mm	± 0,5 mm	2,087 in
<b>D</b>	<b>Pitch, length per piece MD</b>	85 mm	± 1,5 mm	3,346 in
<b>E</b>	<b>Die-cut to web edge</b>	2 mm	± 1,5 mm	0,079 in
<b>G</b>	<b>Antenna to die-cut (MD)</b>	2,5 mm	± 1,5 mm	0,098 in
<b>H</b>	<b>Antenna to die-cut (CD)</b>	2 mm	± 1,5 mm	0,079 in
<b>U</b>	<b>Die-cut corner radius</b>	3 mm		0,118 in
	<b>Thickness of the IC</b>	127 µm	± 15 %	
	<b>Overall thickness of transponder package (excluding IC and siliconized paper)</b>	136 µm	± 10 %	
	<b>Thickness of the siliconized paper</b>	56 µm	± 5 %	

## electrical characteristics

<b>Integrated Circuit (IC)</b>	NXP ICode SLIX2
<b>Air interface protocol</b>	ISO 15 693, ISO 18 000-3 Mode 1
<b>Operating frequency</b>	13,56 MHz
<b>Unloaded resonance frequency</b>	14,10 MHz ± 0,35 MHz
<b>Memory</b>	2.5k bits user memory

## general characteristics of transponder

<b>Operating temperature (electronics parts)</b>	-40 °C / +85 °C	-40 °F / 185 °F
<b>ESD voltage immunity</b>	± 2 kV peak HBM	
<b>Shelf life: From the date of manufacture 2 years in</b>	15 °C / 25 °C, 50 % RH	59 °F / 77 °F, 50 % RH
<b>Bending diameter (D)</b>	> 50 mm, tension less than 10 N	

## delivery form

<b>Transponder format</b>	Die-cut
<b>Transponder face material</b>	Clear PET 12
<b>Transponder backing material</b>	Siliconized Paper 56
<b>Transponder antenna material</b>	Aluminum, crimped coil
<b>Transponder adhesive</b>	Neutral pH Radiation Cured UV Acrylic
<b>labelling temperature</b>	min. +0 °C, min. 32 °F
<b>usage temperature</b>	-20 °C - 80 °C, -4 °F - 176 °F
<b>peel</b>	min. 10 N / 25 mm (FTM 1)
<b>Final inspection</b>	100 %, known faulty ones marked
<b>Minimum delivery yield</b>	97 %
<b>Printability</b>	Needs to be tested by customer

## delivery details

<b>Appearance</b>	Single row reel form
<b>Reel core</b>	Paper core inner diameter 76 mm (3 in)
<b>Transponder alignment</b>	Chip at rear of transponder
<b>Winding of the reel</b>	Face out
<b>Standard reel size</b>	1500 pcs/reel
<b>Package size</b>	3000 pcs/box, Deliveries only in full packages, 3 rolls per box

## bibliotheca label performance guarantee

All bibliotheca RFID tag™ products must pass accelerated aging testing at 85°C and at 85% humidity for 15 weeks which included performance testing. Our entire range of RFID tag™ products, when handled according to our recommended practices, are guaranteed for the lifetime of the item to which they are affixed. Data Retention guaranteed for 50 years with a minimum of 100,000 read/write cycles.

Although we make every effort to ensure information is correct at the time of release, it is possible that specifications and features may vary or change over time. bibliotheca therefore makes no representations or warranties as to the completeness or accuracy of the information contained within this document.

 **bibliotheca**<sup>®</sup>  
transforming libraries